



TECHNICAL SHEET

DESCRIPTION

FINISH OIL N&C is a natural finish suitable for interior wooden floors and furniture. It is distinguished by the following characteristics: ease of application, excellent water resistance, high resistance to wear and the dirt, the absence of flammable solvents and VOC extremely reduced.

TECHNICAL DATA

Appearance of the product neutral:	oily liquid opalescent.
Type:	siccative system based on natural oils and waxes.
Versions:	semi-gloss and matte (clear and colored).
Viscosity (Ford 4):	19 sec.
Specific weight:	0.9 kg / liter
Pot Life:	> 2 h at 25° C
Impregnation time:	20 minutes
Drying surface:	24 hours
Method and Application:	roller, brush, pad, brush with microfibre cloth
Recoat:	after 6 - 8 hours
Application conditions:	between + 15° C and + 25° C with u.r. up to 60%

INDICATIONS

1. Do not apply the product in extremely cold and wet.
2. During application avoid air currents.
3. Acclimate the product before application.
4. It is appropriate to grind the floor in an accurate manner using cards or retinas abrasive in a gradual manner: after grouting grain 80/120/180/220. In this way, we can optimize the work and improve the final appearance.

For any questions covering any changes in operations, contact your technical service.

SURFACE PREPARATION

The surface must be filled, smooth, perfectly clean and free of detaching or residues in general. For the application use containers and clean tools.

PRODUCT PREPARATION

The product is ready to use: It is recommended to shake the container 1-2 minutes before application.
 FINISH OIL N & C should also be used as a primer.

APPLICATION

Apply the first coat of the product in a thin and homogeneous removing excess avoiding drafts. After drying, apply a thin even second hand. For a renewal of finishing oil / wax just one hand on clean, dry surface.

AVERAGE COVERAGE

50-80 gr / sqm. with the use of a roller microfiber short hair (depends on the conditions of the installation surface).

**FINISH OIL N&C**
DESICCANT OIL FINISH
OR WOOD FLOORS**TECHNICAL SHEET****STORAGE**

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight. Protect from frost.

PACKAGING

Drum ME - 1.0 liters, 5.0 liters, 10.0 liters

NOTE

The information contained in this data sheet is based on our best knowledge and preparation.

However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice.

Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS.