



TECHNICAL SHEET

DILUENTE UG3

DILUTION SOLVENT

FOR EPOXY AND POLYURETHANE SYSTEMS

DESCRIPTION

DILUENTE UG3 is composed of a special mixture of solvents that, after the synthesis, they have undergone a process of forced dehydration, making it particularly suitable in a wide spectrum of applications: paint, surface treatment, cleaning and degreasing. This product is specific for solvent-based systems particularly moisture sensitive (glues, paints, primers) formulated polyurethane, epoxy silane, acrylic-urethane, oil-urethane.

TECHNICAL DATA

Appearance:	clear colorless liquid
Type:	mixture of organic solvents
Odor:	characteristic
Specific weight:	0.90 kg / l
Pot Life:	N.A.

INDICATIONS

1. Always work in well ventilated locations, away from sources of heat, or various sources of ignition.
2. For thinning an two-component system add the DILUENTE UG3 only after composing the mixture.
3. Ventilate the area during and after application of the product. For the application using clean containers.

For any questions about changes to operations, contact your technical service.

SURFACE PREPARATION

In applications for cleaning and degreasing, the surfaces to be process must be free of loose parts or other extraneous materials.

PRODUCT PREPARATION

The product is ready for use.

APPLICATION

As a degreasing agent, apply on the area to be cleaned a cloth soaked in VELOSOLV S, leave it on for a few minutes, remove the material by dabbing. Rubbing is not recommended because it can abrade the surface.

As paint thinner, primers, etc. the application should follow the indication of the product.

AVERAGE COVERAGE WITH SHORT NAP ROLLER

N.A. Since this is a thinning product, consumption is very relative: it depends on the conditions and methods of use.

STORAGE

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 ° C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight.

PACKAGING

ME drum 10 Lt.



TECHNICAL SHEET

NOTE

The information contained in this data sheet is based on our best knowledge and preparation. However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice. Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS

DILUENTE UG3

DILUTION SOLVENT

FOR EPOXY AND POLYURETHANE SYSTEMS