



TECHNICAL SHEET

DESCRIPTION

MH UNI is an innovative single-component polyurethane paint for wood floors that replaces the traditional product in solvent with higher performance and lower environmental impact being formulated with a low content of volatile organic substances (VOC). Particularly suitable for floors subject to heavy abrasion (high traffic). Further advantages are at the application level since is a product with high fullness and may be sufficient even a single application to have good aesthetic results.

TECHNICAL DATA

Appearance:	transparent oily liquid.
Type:	modified polyurethane prepolymers.
Ford 4 Viscosity:	20 sec.
Solids content:	> 70%
Minimum application temperature:	+12 °C
Specific weight:	1.2 g / ml
Pot Life:	90 min. at 25 °C
Foot traffic after the application:	36 h at 25 °C

INDICATIONS

1. Do not apply the product in extremely cold and wet.
2. During application avoid air currents.
3. Acclimate the product before application.
4. Smooth the floor accurately using abrasive paper or retinas gradually: after filling grain 80/120; intermediate sanding between coats of paint grain 180/220. In this way, you can optimize the work and improve the final appearance.

For any questions covering any changes in operations, contact your technical service.

SURFACE PREPARATION

The surface must be filled, smooth, perfectly clean and free of detaching or residues in general. For the application use containers and clean tools.

PRODUCT PREPARATION

The product is ready to use: It is recommended to shake the container 1-2 minutes before application. The paint can also be used as a primer.

APPLICATION

Apply the first coat of paint uniform and homogeneous, avoiding drafts. If the surface is not sufficiently covered after complete drying, the floor can be recoated after sanding with fine sandpaper (180 - 220). Aspirate and repaint with one coat of the same product, respect the drying time between coats.

AVERAGE COVERAGE WITH SHORT HAIR ROLLER

80-100 gr / sqm. (depending on the installation surface).



TECHNICAL SHEET

STORAGE

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 ° C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight. Protect from frost.

PACKAGING

ME 5 liter or 10 liter drum

NOTE

The information contained in this data sheet is based on our best knowledge and preparation. However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice.

Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS.

MH UNI

SINGLE COMPONENT HIGH SOLID PAINT

FOR WOODEN FLOORS