



TECHNICAL SHEET

DESCRIPTION

PRIMACRIL W is a primer in consolidating the basis of a special acrylic resin in aqueous emulsion. It is distinguished by the following characteristics: high penetration of the support, excellent resistance to alkali, low emission of VOC exempt from EEC label. With two successive applications of PRIMACRIL W produces a strong reduction for humidity lifts. Specifically to be used with water-based adhesive vinyl and acrylic in laying hardwood floors and ceramic on cement, anhydrite, stone etc.. Also suitable for radian supports.

TECHNICAL DATA

Appearance: opalescent colorless liquid.
Type: acrylic microemulsion.
Dilution: ready to use (possibly with water at 10% max).
Minimum application temperature: +12 °C
Specific gravity: 1.15 kg / L
Pot Life: > 2 h at 25 °C
Foot traffic after application: 3/6 at 25 °C
Waiting time for recoating: 6/8 h at 25 °C

INDICATIONS

1. Before installation, acclimate the wood elements and other products for the installation
2. (adhesives, primers, varnishes) at a temperature between +15 °C and 35 °C.
3. Make sure that the laying environment has a value of relative humidity <70%. 3
4. Do not use in areas of high humidity.
5. Do not use adhesives water-reactive.
6. Ventilate the area during application of the product.

For any questions covering any changes in operations, contact your technical service.

SURFACE PREPARATION

The surfaces to be treated must be free of dust, mold release agents or other foreign materials.

PRODUCT PREPARATION

The standard product as it is ready to be applied.

APPLICATION

Dusting Treatment: To obtain a compact surface, improving the mechanical performance of the parquet is glued to the cement screed. Apply a coat of the product as evenly (roller or brush), leaving it to harden for at least 24 hours in a natural way.

AVERAGE COVERAG WITH ROLLER APPLICATION

Approximately 100 to 200 g/m² hand (dusting and consolidating the surface).

PRIMACRIL W
CONSOLIDATING ACRYLIC WATER
FOR ABSORBENT SUPPORT



TECHNICAL SHEET

STORAGE

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 ° C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight.

PACKAGING

PE tank Lt.10

NOTE

The information contained in this data sheet is based on our best knowledge and preparation. However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice. Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS.

PRIMACRIL W
CONSOLIDATING ACRYLIC WATER
FOR ABSORBENT SUPPORT