



TECHNICAL SHEET

DESCRIPTION

WSA50 is a a filler binder water-based modified acrylic resins. Should be mixed with finer wood dust obtained from the smoothing of the surface being machined (floor or other wood product). It is distinguished by the following characteristics: high filling power, good drying, non-flammable solvents, very low VOC content. This product is suitable for water and solvent based coating systems.

TECHNICAL DATA

Appearance: thick white liquid
 Type: modified acrylic resin in water dispersion
 Minimum application temperature: +12 ° C
 Viscosity (Ford 4): 27/2
 Density: 1.05 Kg / lt
 Sanding: after 40 minutes at 25 ° C
 Application: trowel steel
 Mixing ratio: approximately 1:1 with sawdust
 Pot Life (MIX): > 2 hours

INDICATIONS

1. Use clean containers for the application
2. Shake the container before use.
3. Wait until completely dry before sanding (depending on environmental conditions).
4. Do not use the stucco already mixed after 5 or 6 hours.

For any questions about changes to operations, contact your technical service.

SURFACE PREPARATION

The wood surface must be carefully polished, perfectly clean and free of detaching or residues in general.

PRODUCT PREPARATION

The product itself should be combined and well mixed with fine grinding powder (obtained with grain 100-120).

APPLICATION

Apply the mixture with steel trowel, smoothing all over the floor or other wooden surface. In the case of significant cracks repeat the operation several times in the affected areas only after complete drying of the product that has already been applied.

AVERAGE COVERAG WITH SHORT HAIR ROLLER

50-150 gr / sqm. (depending on the installation surface).

WSA 50

STUCCO WATER BINDER

FOR FLOORS AND WOODEN SURFACES



TECHNICAL SHEET

STORAGE

The product keeps the warranty in its original packaging (not altered) under standard conditions (15-35 ° C and 35-70% RH) for a period of 12 months. It is important to keep the product in a dry and ventilated area away from heat and direct sunlight. Protect from frost.

STORAGE

PE tank of 5 liters or 10 liters

NOTE

The information contained in this data sheet is based on our best knowledge and preparation. However, this cannot be interpreted as a commitment to guarantee, since the means, place of employment and the application conditions are beyond our control. So we do not assume any liability for unauthorized use of the product as the advice given in this application is indicative. In the case where there is any doubt about the application, it is recommended to perform preliminary tests.

The company Viscol s.n.c. therefore reserves the right to change or update this sheet without notice.

Users of the product are advised to check that you have the latest update.

BEFORE USING THE PRODUCT ALWAYS CONSULT MATERIAL SAFETY DATA SHEETS.

WSA 50

STUCCO WATER BINDER

FOR FLOORS AND WOODEN SURFACES